

AIP-4010



IP audio transmitter with line input. For transmitting audio through the local area network LAN. It has 4 level inputs and 4 output relays for event activation and controlling external devices.

It can configure the network parameters automatically.

The perfect solution for large shopping centres, schools, office buildings, etc.

CHARACTERISTICS	IP audio Transmitter. For audio transmission through streaming using multicast through the local area network (LAN). General purpose inputs and outputs. Remote upgrading through software for PC or locally through SD or USB.
INPUTS	1 auxiliary, 2 x RCA and 3.5 mm stereo jack 4 separate programmable inputs for events activation through contact closure, euroblock USB port and SD card reader for software upgrading
OUTPUTS	1 ethernet 10/100 base T, RJ-45 4 separate programmable outputs for opening and closing contacts, euroblock
POWER SUPPLY	100-240 V AC, 16 W
DIMENSIONS	337 x 44.5 x 240 mm depth. 1 U 19' rack
WEIGHT	2.5 kg
ACCESSORIES	Mounts for assembly in 19' rack
SOFTWARE	Software for PC with automatic detection of the AIP series devices connected to the local area network Audio channel creation Remote selection of the audio channel in each receiver Remote adjustment of the configuration parameters Scheduled and real-time messages Firmware upgrading

© 2016 Copyright by FONESTAR SISTEMAS, S.A.