

# Stereo Bluetooth Wireless Audio!

BT-STR Stereo Receiver  
Connect Any Mixer or  
Any Active Cabinet!



From Any Bluetooth Device

## Wireless Systems

### TMW 8000R

- Reception Mode: Diversity
- Carrier Frequency Range: UHF 780 – 865 MHz
- Frequency Response: 50Hz – 15KHz  $\pm$ 3dB
- Oscillation Mode: Quartz Controlled fixed Frequency
- Squelch: Tone Key (32.768 KHz). External Control

### TMW 9144R

- Multi-Channel: 144 Frequencies
- Frequency Band: UHF 470-900 MHz Dependent on Country Regulations
- Receiver Type: PLL UHF Synthesized
- Frequency Response: 50Hz – 15KHz  $\pm$ 3dB
- Modulation Mode: FM (F3E)

### TMW U1.100R

- Channel : Single, 100 Frequencies
- Receiver Type: True Diversity PLL Synthesized
- Frequency Band: UHF (615/638MHZ) or (638/662MHZ)
- Modulation: FM (F3E)
- Frequency Response: 50Hz – 15KHz ( $\pm$ 3dB)

### TMW U2.100R

- Channel : Dual, 100 Frequencies per channel. 200 Total
- Receiver Type: Dual Receiver PLL Synthesized
- Frequency Band: UHF (CHA 615-638/CHB 638-662 MHz)
- Modulation: FM (F3E)
- Frequency Response: 50Hz – 15KHz ( $\pm$ 3dB)

### BT-STR

- Bluetooth V1.1 +EDR
- With LED Display
- With PRE. NEXT / PLAY / PAUSE / VOL / VOL+ / PAIR
- External antenna an help to increase the transmit distance
- More than 20 meters transmit distance in open place

## Technical Specifications

### TMW 8000T

- Carrier Frequency: UHF 780-865MHz
- Microphone Element: Dynamic
- RF Carrier Power: 10mW
- Battery: More than 8 hours
- Antenna: Built in

### TMW 9144T

- Oscillation Mode: PLL UHF Synthesized
- Mic. Capsule: Dynamic
- RF Output Power: 5-50mW (Adjustable 3 Bands)
- Frequency Response: 50Hz – 15KHz  $\pm$ 3dB
- Battery: AA type x 2

### TMW U1.100T

- Frequency band: UHF
- Oscillation Mode: PLL UHF Synthesized
- RF Radiation FCC: 10mW
- Battery: "AA" type x 2pcs (used for more than 6 hours)
- Microphone Capsule: Dynamic Capsule
- Frequency Response: 50Hz-15KHz ( $\pm$ 3dB)

### TMW U2.100T

- Frequency band: UHF
- Oscillation Mode: PLL UHF Synthesized
- RF Radiation FCC: 10mW
- Battery: "AA" type x 2pcs (used for more than 6 hours)
- Microphone Capsule: Dynamic Capsule
- Frequency Response: 50Hz-15KHz ( $\pm$ 3dB)

### RI / T2

- Operating Band: ISM 2.4GHz free band
- One transmitter with one receiver or multi-receiver
- GFSK digital modulation/demodulation
- External antenna can help to increase the transmit distance
- More than 30 meters transmit distance in open place