

WA-2154D



Compact Hi-Fi stereo amplifier, 2 x 15 W RMS, with one optical digital audio or SPDIF input and two auxiliary lines. Headphone output. Suitable for amplifying the TV digital audio output or for listening through headphones. Highly reliable with high quality audio. Compact and robust construction. Highly efficient class D amplification circuit.

CHARACTERISTICS	Compact class D stereo amplifier. Steel case for surface assembly. Digital and analogue audio inputs. Stereo speaker output. Headphone output.
POWER	2 x 15 W RMS at 4 Ohm
PROTECTION	Short-circuit and temperature
RESPONSE	20-20 000 Hz
DISTORTION	Harmonic: 0.06 % at 1 kHz
INPUTS	1 optical SPDIF, toslink 1 coaxial SPDIF, RCA 2 auxiliary lines, 2 x RCA and 3.5 mm stereo jack
OUTPUTS	4-8 Ohm speakers, Euroblock 1 auxiliary line, 2 x RCA 1 headphones, 3.5 mm stereo jack
CONTROLS	Input signal selector Digital input signal selector: optical or coaxial General volume Headphone volume
INDICATORS	LED power indicator LED indicator for input 1 signal
POWER SUPPLY	12 V DC, 2 A with adapter included
DIMENSIONS	205 x 25 x 108 mm depth

WEIGHT

0.6 kg (with adapter included)

© 2015 Copyright by FONESTAR SISTEMAS, S.A.